



Belgray 75W140 Gear Oil

PRODUCT DESCRIPTION

Belgray 75W-140 Gear Oil is a heavy duty, extreme pressure, GL-5 synthetic gear lubricant.

Belgray 75W-140 is engineered with state-of-the-art advanced additive chemistry which includes extreme pressure, as well as rust, oxidation and corrosion inhibitors. **Belgray 75W-140** is designed to provide supreme protection of gears and bearings operating under a wide variety of load conditions and temperatures.

FEATURES/BENEFITS

- Outstanding Extreme Pressure Performance
- Limited Slip Differentials
- High Film Strength
- Superior Low-Temperature Performance
- Outstanding Shear Stability
- All Season Performance
- Better Operating Performance
- Improved Fuel Mileage
- Extended Drain Intervals
- Excellent Oxidation Resistance

APPLICATIONS

- API GL-5
- API MT-1
- MIL-PRF-2105E
- J2360
- Mack GO-J
- PG-2 Limited Slip

TEST (Method)	75W140
Viscosity, cSt @ 40°C	169.5
Viscosity, cSt @ 100°C	25.3
Viscosity Index	183
Brookfield Viscosity, ASTM D2983 cP @ -40°C	124,000
Color	1.0
Flash Point (COC), C° (F°)	226 (438)
Pour Point, C° (F°)	-40 (-40)
Gravity, Specific, ASTM D1298	.8458
Density, lbs/gal	7.05
Copper Corrosion, ASTM D130	Pass
Foam Test, ASTM D892	Pass
FZG, Failure Stage	>12